

MARKEN GmbH

Gildestr. 2 - 48356 Nordwalde

+49 2573 97 95 200

+49 2573 97 95 202

Applications : For the automatic cutting of hydraulic hoses with or without metal reinforcement, thermoplastic, PTFE

600 S



CONTROL

- Touch Screen
- Includes PC control with networking and database function
- Includes Marken Kit Cutting Software
- Includes Adhesive Label application system

ADVANTAGES

- Immediate productivity increase
- High accuracy
- "Wet" cut for a clean an square cut and an important reduction in fumes

TECHNICAL SPECIFICATIONS

Application / Max. Capacity

Capacity	3/4" 2wire 1"1 wire hose
Drive	0,37kW double driven rollers (Optional double drive belts)
Type of cut	Smooth blade 300mm lubricated
Speed	500 pieces per hour at 1 meter 1/2" 1wire hose (with labels)
Noise level	< 80db
Electrics	Motor 4KW 400V 3Ph
Pneumatics	7 bar
Weight	680 Kg
Dimensions	1300 X 910 X 1600 mm
Cooling of blade	Anti-corrosive emulsion
Accuracy	0,3% of requested length

OPTIONS

- Ink-jet printing :
 - Part numbers
 - Client's name..
- Mechanical Depth Marking
- Powered Payout system
- Powered Conveyor System
- Collection Trough System
- Memory of part numbers
- Splice detector

ACCESSORIES

- Reel racks
- Decoilers
- Electric coilers or spoolers

MARKEN MANUFACTURING

2081 E. Center Circle, Plymouth MN 55441 USA

ISO 9001 : 2008 CERTIFIED