

MARKEN GmbH

Gildestr. 2 - 48356 Nordwalde

+49 2573 97 95 200

+49 2573 97 95 202

K 285

Applications : for crimping of hydraulic hoses up to 3" and Industrial hoses up to 6"



ADVANTAGES

- Working height adjusts from 350mm to 1016mm

OPTIONS

- Control-Touch screen or Micrometer

DIE SIZES

N°:	Crimping range:	Length:
4	4.0-6.0	56mm
6	6.0-8.0	56mm
8	8.0-10.0	56mm
10	10.0-12.0	56mm
12	12.0-17.0	56mm
17	17.0-20.0	56mm
20	20.0-24.0	70mm
24	24.0-27.0	70mm
27	27.0-30.0	70mm
30	30.0-33.0	70mm
33	33.0-39.0	70mm
39	39.0-48.0	80mm
48	48.0-57.0	110mm
57	57.0-66.0	110mm
66	66.0-72.0	100mm
72	72.0-76.0	125mm

TECHNICAL SPECIFICATIONS

Indicative capacity:

Hydraulic	3" 6 wire
Industrial	6"
ANSI 150 lb Flange	6"
ANSI 300 lb Flange	4"
Crimp range	4 to 210mm
Theoretical crimp force	400 tons
Crimping per hour	850 (cycle time: 9s)
Opening travel	+55mm
Opening witouht dies	285mm
Motor	5,5kW - 208/480V 3Ph
Voltage options	230V 3Ph or 480V 3 Ph
Master die length	150mm
Weight/dimensions	600 Kg 1120 x 1020 x 1680mm

OTHER SIZES AVAILABLE

Ø9/15/18/21/36/42/45/51
/54/60/73/80/86/90/95/99
/112/117/122/130/136/146
/156/166/176/186/196/20
6/215

MARKEN MANUFACTURING

2081 E. Center Circle, Plymouth MN 55441 USA

ISO 9001 : 2008 CERTIFIED